



Cadman's PT Gold is post tension with years of research.

- High early strength – guaranteed 3000 psi at 64 hours and 5000 psi at 28 days.
- PT Gold means a reduction in construction schedule.
- Designed for a predictable construction schedule and to ensure improved finishing quality.
- Designed to reduce shoring costs.
- Guaranteed low shrinkage (0.042 or less).
- Low water to cement ratio means reduced permeability.
- Automatic adjustment of aggregate proportions to maximum density which means consistency from day to day, from location to location.

PT GOLD - POST TENSION MADE EASY!

Our goal in developing this mix was to offer our customers the best possible mix design specifically for use in post tension slabs. Recognizing the increasing popularity for this method of construction, Cadman has spent years testing various solutions, both in our lab and in the field.



We believe PT Gold provides the complete solution for project owners, contractors, architects, engineers, and finishers! Through years of research and testing, we are able to guarantee consistency in a mix design with all the characteristics our customers want -

- High early strength
- Low shrinkage
- Predictability
- Reduced permeability
- Maximum density
- Ease of placement

Cadman went to the regions' experts to get their input.

"Cadman has a clear understanding of engineers' concerns and building performance requirements in today's post-tensioned structures. Engineers today need the ability to specify a range of concrete performance levels to suit the project. Cadman is offering that flexibility with PT Gold".

- Mark D'Amato, Principal, DCI Engineers

